



New series K3
of Gram indicators



DESIGNED
IN EUROPE



Professional performance

► Functions:

- Memory for 100 items with alphanumerical code.
- Classification or verification by weight with viewing in 3 bright colours.
- Piece counter function with weight memory by unit for 100 items.
- 4 Autohold levels for weighing large-size objects.
- Memory zero for weighing tanks and silos.
- Port for barcode scanner.
- Accumulation of weighings with aggregation.
- Automatic, normal or set tare.
- Memory for 20 preset tares.
- Ticket printing.



► Adaptable

Can be hung from the wall without the need for a support, or installed on a column.



► Protection against liquids and dust

Designed for working in humid or dusty environments. With IP-65 protection.



► Weight verification

The visor changes colour to indicate whether the weight is above (red colour), below (yellow colour) or within (green colour) of the set range.



► Printing of results

Connection with our printers, with and without (wireless) cable. Prints three initial lines and one at ticket end, including our Z3 THS software for data input from PC. With our Q2 labelling machine it prints the data in an adhesive label format. Connects with our remote display via cable or wireless.



► USB Direct, what you always wanted

With our direct cable between the indicator and your PC or MAC, the weighing data will appear in any application or document you have open. Without intermediate software, without installation, simple and effective.

Model	K3
Reference	6170
Resolution	100,000 div.
Weight ranges	≈<2
Linearity	10 points
Calibration weight	Selectable
Weighing units	g(kg), lb, oz
Piece counter quantities	10, 20, 30, 50, 100
Display	Backlit LCD
Segments	6 digits
Digit height (mm)	25
Connectivity	RS 232-C, 3-relay output (opt.), Wi-Fi (opt.)
Material	ABS
Sealing protection	IP-65
Power	230 V / 50 Hz [Euro] 11 V AC
Battery duration	30 / 60 hours
Working temperature	+5°C / +35°C
External dimensions (mm)	220 x 182 x 86
Total net weight (kg)	1.5
Packaging dimensions (mm)	325 x 235 x 165
Total weight with packaging (kg)	2.3
RRP (€)	---

Ref.	Options	RRP (€)
32330	3-relay output	---
32277	RS-232 second output	---
3776	Wireless K connection	---

Ref.	Accessories	RRP (€)
32332	Tare pedal	---
5263	RD3 repeater indicator (RS-232)	---
6950	RD3W repeater indicator (Wireless)	---
70814	Q2 labelling machine	---
70034	PR4 printer (RS-232)	---
70035	PR4W printer (Wireless)	---
70036	PR6 printer (RS-232)	---
70037	PR6W printer (Wireless)	---
4877	Virtual Key software for PC	---
32278	Stainless steel U wall support	---
31661	Wall support in painted steel with ABS swivel joint	---
61084	Direct K USB cable	---
33205	RS-232 cable to RD3 or PC K, 1.5 m	---
3738	RS-232 cable to RD3 or PC K, 4 m	---
32294	RS-232 cable to K Printer	---

External dimensions (mm)

More information

K3



